
















Vinyl HDF finished floor WOOD DECORS wear layer 0,3 mm

			HDF Sound
	Dimensions & thickness	EN 427 & EN 428	1235 × 230 × 8,2 mm > Conceptfloor Clever Line 1.2 1235 × 230 × 9,8 mm > LICO Eco Line 1.5 1235 × 230 × 8,5 mm > Conceptfloor Fashion Line 1.5 1235 × 230 × 8,5 mm > LICO Eco Line 1.5 1235 × 230 × 9,5 mm > Conceptfloor Eco Line 1.5
	Classification	EN 16511	23/32
	Total weight	EN 430	7.800 g/m ² > Conceptfloor Clever Line 1.2 8.100 g/m ² > LICO Eco Line 1.5, Conceptfloor Fashion Line 1.5 9.000 g/m ² > LICO Eco Line 1.5, Conceptfloor Eco Line 1.5 9.500 g/m ² > LICO Eco Line 1.8
	Impact sound reduction	EN ISO 717-2	14 dB > Conceptfloor Clever Line 1.2 14 dB > LICO Eco Line 1.5, Conceptfloor Fashion Line 1.5 16 dB > LICO Eco Line 1.5, Conceptfloor Eco Line 1.5 16 dB > LICO Eco Line 1.8
	Effect of castor chair	EN 425	Typ W
	Reaction of fire	EN ISO 9239-1	Bfl-s1
	Thermal resistance	EN 12524	ca. 0,08 m ² K/W > Conceptfloor Clever Line 1.2 ca. 0,08 m ² K/W > LICO Eco Line 1.5, Conceptfloor Fashion Line 1.5 ca. 0,088 m ² K/W > LICO Eco Line 1.5, Conceptfloor Eco Line 1.5 ca. 0,088 m ² K/W > LICO Eco Line 1.8
	Dimensional stability	EN 434	< 0,05%
	Residual indentation	EN 433	max. 0,03 mm
	Lightfast	ISO 105	6/7
	Resistance to chemicals	EN 423	Good durability
	Emissions value		according to AgBB
	Swellness value 24h	EN 317	< 8%

	Locking strenght	ISO 24334	> 450 kg/lfm
	Reaction to static electricity	EN 1815	< 2,0 kV
	Coefficient of friction	EN 51130	R10